



Die Number	Dim. (B)	Dim. (H)	Dim. (P)	Dim. (T)	Dim. (R)	Dim. (R1)	WT. (LBS/FT)	WT. (KGS/MT)	Toronto	Ohio
S-10509	3.000	1.410	0.170	0.170	0.270	0.100	1.423	2.118		✓
S-10510	3.000	1.498	0.170	0.258	0.270	0.100	1.735	2.581		✓
S-10511	3.000	1.596	0.170	0.356	0.270	0.100	2.082	3.098		✓
S-10512	4.000	1.580	0.180	0.180	0.280	0.110	1.852	2.757		✓
S-10513	4.000	1.647	0.180	0.247	0.280	0.110	2.169	3.227		✓
S-10514	4.000	1.720	0.180	0.320	0.280	0.110	2.513	3.740	✓	✓
S-10515	5.000	1.750	0.190	0.190	0.290	0.110	2.324	3.458		✓
S-41	5.000	1.885	0.190	0.325	0.290	0.110	3.120	4.643		✓
S-24114	6.000	1.250	0.186	0.188	0.250	0.125	2.203	3.278		✓
S-43	6.000	1.920	0.200	0.200	0.300	0.120	2.836	4.220		✓
S-10516	6.000	1.945	0.200	0.225	0.300	0.120	3.013	4.483		✓
S-10517	6.000	2.034	0.200	0.314	0.300	0.120	3.643	5.421		✓
S-45	6.000	2.157	0.200	0.437	0.300	0.120	4.514	6.717		✓
S-10518	7.000	2.110	0.210	0.230	0.310	0.130	3.554	5.289		✓
S-26337	7.000	2.194	0.210	0.314	0.310	0.130	4.248	6.321		✓
S-47	8.000	2.290	0.220	0.250	0.320	0.130	4.267	6.350		✓
S-10519	10.000	2.600	0.240	0.240	0.340	0.140	5.297	7.883		✓
S-25630	12.000	2.960	0.280	0.300	0.380	0.170	7.215	10.737		✓