

## RECTANGULAR BARS, FULL ROUND EDGES



DIE #	DIMENSIONS		WEIGHT		LOCATIONS		
	W	T	LB/FT	KG/M	T	O	M
S-4276	0.703	0.312	0.234	0.348	V		V
S-4922	0.750	0.125	0.111	0.165	V	V	V
S-21963	0.750	0.188	0.157	0.234		V	V
S-21964	0.750	0.250	0.205	0.305		V	V
S-2299	1.000	0.250	0.280	0.417	V		V
S-23745	1.125	0.125	0.162	0.241	V	V	V
S-24936	1.250	0.375	0.518	0.771	V		V
S-2250	1.375	0.375	0.572	0.851	V		V
S-13825	1.500	0.125	0.217	0.323	V		V
S-7348	1.500	0.156	0.270	0.402	V		V
S-2174	1.500	0.250	0.427	0.635	V	V	V
S-13141	1.500	0.500	0.822	1.223		V	V
S-13822	1.750	0.156	0.316	0.470	V		V
S-2202	1.750	0.750	1.407	2.094	V		V
S-2173	2.000	0.125	0.291	0.433	V		V
S-13823	2.000	0.156	0.363	0.540	V	V	V
S-10077	2.000	0.188	0.434	0.646	V	V	V
S-2269	2.000	0.250	0.575	0.856	V	V	V
S-2266	2.000	0.375	0.850	1.265	V	V	V
S-15348	2.000	0.500	1.117	1.662		V	V

DIE #	W	T	LB/FT	KG/M	T	O	M
S-14285	2.000	0.500	1.117	1.662	V		V
S-13824	2.250	0.219	0.569	0.847	V		V
S-26688	2.340	0.205	0.555	0.826		V	V
S-2329	2.500	0.250	0.722	1.074	V		V
S-2175	3.000	0.250	0.870	1.295	V		V
S-2267	3.000	0.375	1.292	1.923	V		V
S-5424	3.000	0.500	1.706	2.539	V		V
S-9489	3.000	1.000	3.286	4.890	V		V
S-2421	3.500	0.250	1.017	1.513	V		V
S-2887	3.688	0.125	0.540	0.804	V		V
S-2298	4.000	0.250	1.165	1.734	V	V	V
S-2248	4.000	0.375	1.735	2.582	V	V	V
S-5016	4.000	0.500	2.296	3.417	V		V
S-5423	4.000	1.000	4.466	6.646	V		V
S-13987	4.500	0.375	1.956	2.911	V	V	V
S-2302	5.000	0.250	1.460	2.173	V	V	V
S-2341	5.000	0.375	2.177	3.240	V		V
S-27107	5.000	0.500	2.887	4.296		V	V
S-2172	6.000	0.250	1.755	2.612	V		V
S-2268	6.000	0.375	2.620	3.899	V		V
S-5419	6.000	0.500	3.476	5.173	V	V	V
S-22055	6.000	0.750	5.168	7.691		V	V
S-5422	6.000	1.000	6.826	10.158	V		V
S-4952	7.000	0.250	2.050	3.051	V		V
S-12466	7.000	0.500	4.067	6.052	V		V
S-5420	8.000	0.375	3.505	5.216	V		V
S-5421	8.000	0.500	4.656	6.929	V		V
S-5693	8.000	1.000	9.186	13.670	V	V	V
S-5829	10.000	0.375	4.390	6.533	V		V
S-6875	10.000	0.500	5.836	8.685	V	V	V